

4000 SPECIFICATIONS

Conveyor	Rubber Mat
Cutting Head	Full Floating Cutter Head
Width of Cut	16" (406 mm) / 23" (584mm) / 24" (610 mm)
Length of Cut	up to 100" (2540 mm)
Thickness of Cut	Hydraulically Adjustable
Pallet Size	48" (1.2 m) x 48" (1.2 m)
Cutter Drive.....	Variable Hydraulic
Conveyor Drive.....	Variable Hydraulic
Cutting Blades	Standard with Fingers / V-Blade
Construction	High Strength Steel Weldment
Total Weight	18641 lbs. (8955 kg.)
Overall Length	296" (7518 mm) (Less Ski)
Overall Width	124" (3150 mm) (Less Toe Guard)
Shipping Width	91" (2312 mm)
Overall Height.....	104" (2642 mm) (Less Strobe) (112.5" w/Mast Sensor)
Pallet Configuration.....	Pyramid or Flat Top
	Upper Level Squeeze Function
Flap Control.....	Automatic

4000 ENGINE, TIRE & CAB SPECIFICATIONS

Caterpillar	I-4. Diesel - Four Stroke Cycle
Displacement	4.4L (269 cu.in.)
Aspiration	Turbocharged After-cooled
Horsepower	127 HP @ 2200rpm
Torque	309 lb-ft. @ 2200rpm - 380 lb-ft. @ 1400 rpm
Front Tires	550/45 R22.5 Flotation (Optional 380/75 R20)
Rear Tires	650/55 R22.5 Flotation Radial
Cab	Deluxe Cab
Seat.....	Deluxe Swivel Air Suspension



KESMAC INC.
 TEL: 905-476-6222 • 1-888-341-5113 FAX: 905-476-6744
 US Parts TEL: 1-800-314-1008
 23324 Woodbine Avenue, Keswick, Ontario L4P 3E9
 email: info@kesmac.com • www.brouwerturf.com



Specifications subject to change without notice or obligation.
 Printed in Canada 01/16

HARVESTER

4000

AUTOMATIC ROLL SOD HARVESTER

Setting New Standards Worldwide
Turf Industry Leaders in Service and Innovation



