

ROBOMAX JD™ SPECIFICATIONS

Conveyor	Rubber / Mintex
Cutting Head	Full Floating Cutter Head
Width of Cut	16" (406 mm) / 23" (584 mm) / 24" (610 mm)
Length of Cut	up to 100" (2540 mm)
Thickness of Cut	Hydraulically Adjustable
Pallet Size	48" (1.2 m) x 48" (1.2 m), 1.0 m x 1.2 m, 0.8 m x 1.2 m
Cutter Drive	Variable Hydraulic
Conveyor Drive	Variable Hydraulic
Cutting Blades	Standard with Fingers / V-Blade
Construction	High Strength Steel Weldment
Total Weight	21604 lbs. (9820 kg.)
Overall Length	270" (6858 mm)
Overall Width	168" (4267 mm)
Transport Width	140" (3556 mm)
Overall Height	103" (2616 mm)
Pallet Configuration	Pyramid or Flat Top
Flap Control	Upper Level Squeeze Function Automatic

TRACTOR SPECIFICATIONS

John Deere	6105M / 6110M
Power	6105 105 HP Engine
Transmission	24 Speed AutoQuad PLUS
Steering	Hydrostatic Power
Traction	Standard 4WD
Front Tires	400/55-225 Flotation
Rear Tires	650/55 R26.5 Flotation Radial
Engine	4.5L PowerTech Single Variable Geometry Turbocharger
Cab	Deluxe Cab
Seat	Deluxe Swivel Air Suspension w/Training Seat



KESMAC INC.
 TEL: 905-476-6222 • 1-888-341-5113 FAX: 905-476-6744
 US Parts TEL: 1-800-314-1008
 23324 Woodbine Avenue, Keswick, Ontario L4P 3E9
 email: info@kesmac.com • www.brouwerturf.com



Watch the Video on YouTube

Specifications subject to change without notice or obligation.
 Printed in Canada 01/16



ROBOMAX JD

AUTOMATIC ROLL SOD HARVESTER

Setting New Standards Worldwide
Turf Industry Leaders in Service and Innovation



